

PFS3008-8GT-60

8-Port Gigabit Ethernet PoE Switch with 4-Port PoE



Product Overview

PFS3008-8GT-60 is a 8-port Gigabit Ethernet switch, which provides 4*10/100/1000Mbps PoE port, 4*10/100/100Mbps Ethernet ports and supports Hi-PoE power supply.

Features

- Layer two commercial switch
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- MAC auto learning, aging, MAC address capacity is 8K
- Supports MDI/MDIX self-adaptation
- RJ45 port supports 10/100/1000 Mbps self-adaptation
- Supports IEEE802.3af and IEEE803.3at power supply standards
- Adopts metal enclosure
- Supports Hi-PoE 60W
- Supports DC 48-57V power supply

Technical Specification

Model	PFS3008-8GT-60
Ethernet Port	4*10/100/1000Mbps PoE ports 4*10/100/1000Mbps ports
PoE Power Consumption	Port1≤60W, Port2-4≤30W, Totals60W
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	20Gbps
Packet Forwarding Rate	11.9Mpps
Packet Buffer Memory	1.5Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC48~57V power adapter
Lightning Protection	Common Mode 2KV Differential Mode 0.5KV
Working Temperature	-10°C~+55°C
Weight	0.49kg
Dimension(W×D×H)	190mm×100mm×30mm