

# DH-PFS3110-8P-96

## 8-Port PoE Switch (Unmanaged)



### Features

- Two-layer industrial PoE switch
- MAC auto study and aging, MAC address list capacity is 8K
- Support IEEE802.3af, IEEE802.3at standard
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- Industrial wide temperature design

### Technical Specification

Model	DH-PFS3110-8P-96
Ethernet Port	1*1000 Base-X 1*10/100/1000 Base-T 8*10/100 Base-T (PoE power supply)
PoE Power Consumption	Each power ≤30W, Totals≤96W
PoE Protocol	IEEE802.3af, IEEE802.3at
Switching Capacity	7.6G
Packet Forwarding Rate	4.17Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC48~57V
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	-30°C~65°C
Weight	540g
Dimension(W×D×H)	150mm×100mm×42mm

### Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode