

DS-2CC51A2P(N)-DG1



Key Features

- Compact design
- SONY CCD
- Min. illumination: 0.002 Lux @ F1.4
- Auto white balance, auto gain control, electronic shutter control and backlight compensation
- Internal Synchronization

Specification

Model Parameter	DS-2CC51A2P(N)-DG1
	650 TVL CCD Mini Camera
Camera	
Image Sensor	1/3" SONY CCD
Signal System	PAL/NTSC
Effective Pixels	PAL: 976 (H) × 582 (V) NTSC: 976 (H) × 494 (V)
Min. Illumination	0.002 Lux @ (F1.4, AGC ON) 0.006 Lux @ (F2.5, AGC ON)
Shutter speed	PAL: 1/50 s to 1/100,000 s NTSC: 1/60 s to 1/100,000 s
Lens	3.7 mm @ F2.5 (2.8 mm optional)
	Angle of view: 70° (3.7 mm)
Lens Mount	M12
Day & Night	Electronic
Horizontal Resolution	700 TVL

Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
General	
Working Temperature/Humidity	-30 °C - 60 °C (-22 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 1 W
Dimensions	30 × 30 × 19 mm (1.18" × 1.18" × 0.75")
Weight	200 g (0.44 lbs)

Order Models

DS-2CC51A2P-DG1

DS-2CC51A2N-DG1

Dimensions

