

DS-1271ZJ-135


Pendent Mounting Bracket for

Dome Camera

Features:

- Aluminum alloy material with surface spray treatment
- Waterproof design
- Cable hole on bracket makes the feature better
- Design of cap is for convenient wiring

Dimension:





Order Model:

DS-1271ZJ-135

Parameter:

Model	DS-1271ZJ-135
	Pendent Mounting Bracket for
Parameters	Dome Camera
Appearance	Hik White
Material	Aluminum Alloy
Dimension	136×565mm
Weight	1350g

Notice:

- The bracket should be installed on flat wall
- Waterproof rubber is necessary for outdoor application
- The wall must be capable of supporting over 3 times as much as the total weight of the camera and the mount.
- The maximum load capacity of the bracket is 4.5KG

Model Suitable:

DS-2CD2712F-I(S), DS-2CD2732F-I(S), DS-2CC52xxP(N)-VP series, DS-2CC52xxP(N)-AVPIR2 series

Installation Step:


(1) Choose the appropriate wall to install the bracket and thread the cable



(5) Install the camera to the adaptor

and fix with screw

(2) Connect pole and adapter; thread cable and screw up



A & B are tightening screw 6 Complete the fixation and

(3) Screw up and complete the fixation of adapter and pole



7 Adjust the view of angle



(8) Installation complete



(4) Take off lower dome and lining

and install lower dome





Note: The actual dome camera may vary from the picture above.