

DH-IPC-HFW1320S-W

3MP HD Wi-Fi IR Mini Bullet Camera



Features

- 1/3" 3Megapixel progressive scan CMOS
- H.264&MJPEG dual-stream encoding
- Max 20fps@3M(2304×1296)&25/30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3.6mm fixed lens (2.8mm optional)
- Max. IR LEDs Length 30m
- IP67
- Micro SD card slot, up to 128GB
- Easy4ip cloud support
- Wi-Fi support

DH-IPC-HFW1320S-W

Technical Specifications


Model		DH-IPC-HFW1320S-W
Camera		
Image Sensor		1/3" 3Megapixel progressive scan CMOS
Effective Pixels		2304(H) × 1536(V)
Scanning System		Progressive
Electronic Shutter Speed		Auto/Manual, 1/3(4)s~1/100000s
Min. Illumination		0. 1Lux/F2.0(Color), 0Lux/F2.0(IR on)
S/N Ratio		More than 50dB
Video Output		N/A
Camera Features		
Max. IR LEDs Length		30m
Day/Night		Auto(ICR)/Color/B/W
Backlight Compensation		BLC / HLC / DWDR
White Balance		Auto/Manual
Gain Control		Auto/Manual
Noise Reduction		3D
Privacy Masking		Up to 4 areas
Lens		
Focal Length		3.6mm(2.8mm optional)
Max Aperture		F2.0(F2.0)
Focus Control		Manual
Angle of View		H: 77°(100°)
Lens Type		Fixed lens
Mount Type		Board-in Type
Video		
Compression		H.264/ H.264H/H.264B/MJPEG
Resolution		3M(2304×1296)/1080P(1920×1080)/720P(1280×720)/ VGA(640×480)/QVGA(320×240)
Frame Rate	Main Stream	3M(1 ~ 20fps)/1080P(1 ~ 25/30fps)
	Sub Stream	VGA/QVGA(1 ~ 25/30fps)
Bit Rate		H.264: 32kbps~8192kbps
Corridor Mode		Support
Audio		
Compression		N/A
Interface		N/A
Network		
Ethernet		RJ-45 (10/100Base-T)
Wi-Fi		Wi-Fi(IEEE802.11b/g/n) 50m(open field)
Protocol		IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Compatibility		ONVIF, CGI

DH-IPC-HFW1320S-W

Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD card, up to 128GB
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
General	
Power Supply	DC12V
Power Consumption	<5.5W(IR on)
Working Environment	-30°C~+50°C, Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	N/A
Dimensions	Φ 70mm×165mm
Weight	0.49Kg with package

DH-IPC-HFW1320S-W

Dimensions (mm)



Accessories (optional)

	
PFA121	PFA152

Dahua Technology Co., Ltd.

1187BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuasecurity.com

*Design and specifications are subject to change without notice.

© 2016 Dahua Technology Co., Ltd.