

DH-TPC-SD8620

Thermal Network Hybrid Dome Camera



- 640*512 VOx uncooled thermal sensor technology
- Athermalized Lens(thermal),Focus-free
- 1/1.9" 2Megapixel progressive scan Exmor CMOS
- Powerful 30x optical zoom
- Support temperature measurement
- Support Fire detect&alarm
- Max 240°/s pan speed, 360° endless pan rotation
- Up to 300 presets, 5 auto scan, 8 tour, 5 pattern
- 7/2 alarm in/out
- Micro SD memory, IP66



System Overview

Featuring a dual lens, speed dome camera, this series provides an all-in-one solution for capturing long distance video surveillance for outdoor applications. Together with Thermal and Starlight Technology, the camera is the perfect solution for dark, long rang monitoring applications. The series combines one thermal camera for monitoring in total darkness and one visible camera with starlight feature and motorized lens for confirming details.

Functions

Uncooled Vox Technology

Dahua thermal cameras use uncooled Vox sensor technology . Because of small size and better performance, it's cost-effective solution for thermal security.

High Sensitivity

High thermal sensitivity(<40mK) makes cameras capture more image details and temperature difference information.

Fire Detect&Alarm

With built-in Fire detect function, the camera has the ability to detect fire in a long distance. because thermal camera is sensitive to temperature, so the accuracy of Fire detect will be higher than visible camera. especially useful for forest fire prevention.

Intelligent Video System (IVS)

With built-in intelligent video analytics, the camera has the ability to detect and analyze moving objects for improved video surveillance. The camera provides optional standard intelligence at the edge allowing detection of multiple object behaviors such as abandoned or missing objects. IVS also supports Tripwire analytics, allowing the camera to detect when a pre-determined line has been crossed.

Auto-tracking

The camera supports auto-tracking. The tracking action can be triggered manually or automatically by defined rules. Once rules are triggered, the camera can zoom in and track the defined target automatically.

Environmental

With a temperature range of -40 °C to +70 °C (-40 °F to +158 °F), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP66 rating makes it suitable for demanding outdoor applications. For environments with rain, sleet, snow and fog, an integrated wiper provides users with clear visibility at all times.

Protection

Supporting ±25% input voltage tolerance, this camera suits even the most unstable conditions for outdoor applications. Its 6KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification

Thermal Camera

Image Sensor	Uncooled VOx Microbolometer
Effective Pixels	640(H)x512(V)
Pixel Size	17um
Thermal Sensitivity(NETD)	<40mK@f/1.0
Spectral Range	7~14um
Image Setting	Brightness/Sharpness/ROI/DDE/AGC/FFC/3D DNR
Color Palettes	14(Whitehot/Blackhot/Ironrow/Icefire/ Fusion/Rainbow/Globow/Iconbow1/ Iconbow2 .etc)

Thermal Lens

Lens Type	Fixed		
Focus Control	Athermalized,Focus-free		
Focal Length	25mm	35mm	50mm
Angle of View	25** 20 °	18** 14 °	12.4** 9.9°
Effective Distance ^① Man(1.8m*0.5m)	D ^② :950m R ^③ :230m I ^④ :120m	D:1300m R:320m I:160m	D:1700m R:450m I:220m
Effective Distance Vehicle(2.3m*2.3m)	D:2800m R:720m I:360m	D:4000m R:1000m I:500m	D:5100m R:1400m I:700m

Visible Camera

Image Sensor	1/1.9" Exmor CMOS
Effective Pixels	1944(H) x 1092(V), 2 Megapixels
Electronic Shutter Speed	1/1 ~ 1/30,000s
Min. Illumination	Color: 0.001Lux@F1.5; B/W: 0.0001Lux@F1.5;
S/N Ratio	More than 56dB
IR Distance	150m
IR On/Off Control	Auto/Manual
IR LEDs	9

Visible Lens

Focal Length	6mm~180mm
Max Aperture	F1.5 ~ F4.3
Angle of View	H: 61.2° ~ 2.32°
Optical Zoom	30x
Focus Control	Auto / Manual
Close Focus Distance	100mm~ 1000mm (328ft~3280ft)

PTZ

Pan/Tilt Range	Pan: 0° ~ 360° endless;Tilt:-20° ~ 90°
Manual Control Speed	Pan: 0.1° ~200° /s; Tilt: 0.1° ~120° /s

Preset Speed	Pan: 0.1° ~240° /s ;Tilt: 0.1° ~200° /s
Preset	300
PTZ Mode	5 Pattern, 8 Tour, Auto Pan, Auto Scan
Speed Setup	Human-oriented focal length/ speed adaptation
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period
Protocol	DH-SD, Pelco-P/D (Auto recognition)

Video

Compression	H.264(Base profile/Main profile/High profile)/ MJPEG
Frame Rate	Main Stream: Thermal: 1280*1024 (default)/ 720P @30fps Visible: 1080P (default)/720P@30fps Sub Stream: Thermal: 640*512 (default)/ 320*256 @15fps Visible: CIF(default)/D1@15fps
Bit Rate Control	CBR / VBR
Bit Rate	H.264: 1280K ~14Mbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto, ATW,Indoor, Outdoor, Manual
Noise Reduction	Ultral DNR
Motion Detetion	Off / On (4 zone, Rectangle)
Region of Interest	off/On (4 zone)
Electronic Image Stabilization (EIS)	NA
Defog	Off/On
Digital Zoom	24x
Flip	180°
Mirror	Off/On
Privacy Masking	Off / On (4 area, Rectangle)

Audio

Compression	G.711a/G.711Mu/AAC
-------------	--------------------

Intelligent Function

Auto Tracking	Support
IVS (optional)	Tripwire, Intrusion, Object Detection(People&Vehicle), Abandon detection, Missing detection, Fire detect& alarm .etc.
Tracking Trigger Mode	Manual / Auto (alarm triggered)
Tracking Trigger Event	Targeting, Zoom, Tracking, Recording, Snapshot, Alarm and etc.

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Interoperability	ONVIF PSIA CGI
Streaming method	Unicast / Multicast
Max. User Access	20
Edge Storage	micro SD (128GB) Memory status display (Normal / Error / Active / Formatting / Lock), NAS (Network Attached Storage), Local PC for instant recording
Web Viewer	<IE11, <Chrome44, Firefox
Management Software	Smart PSS, DSS
Smart Phone	Android, ios

Certifications

Certification	CE (EN 60950:2000) FCC (FCC Part 15 SubpartB)
---------------	--

Interface

Video Interface	1.0Vp-p/75Ω, PAL / NTSC (HDCVI Optional)
Audio Interface	Input/Output 1 Input / 1 Output
RS485	Support
Alarm	7/2 In/Out

Electrical

Power Supply	24V AC ±25%
Power Consumption	Max. 38W (24V AC, Heater on),

Environmental

Operating Condition	-40°C ~ +70°C (-40°F ~ +158°F) / Less than 95% RH * Start up should be done at above -40°C (-40°F)
Storage Conditions	-40°C ~ +70°C (-40°F ~ +158°F) / Less than 95% RH
Ingress Protection	IP66

Construction

Casing	Metal
Dimensions	Φ240mm x 464mm (Φ9.45" x 15.04")
Net Weight	6.8Kg (14.99 lb)
Gross Weight	9.5Kg(20.94 lb)

Note:

- ① Effective distance values shown are nominal values and should be used as estimates only. Exact value calculations depend on a wide variety of conditions.
- ② D: Detection
- ③ R: Recognition
- ④ I: Identification

Ordering Information

Type	Part Number	Description
DH-TPC-SD8620	DH-TPC-SD8620P-A25 DH-TPC-SD8620N-A25	Thermal:640*512 25mm lens Visible:2Mp 30X
	DH-TPC-SD8620P-A35 DH-TPC-SD8620N-A35	Thermal:640*512 35mm lens Visible:2Mp 30X
	DH-TPC-SD8620P-A50 DH-TPC-SD8620N-A50	Thermal:640*512 50mm lens Visible:2Mp 30X

Accessories

Included:



PFA111
Mount Adapter



AC24V/3A
Power Supply

Optional:



PFA140
Power box



PFB300C
Ceiling Mount



PFB303W
Wall Mount



PFA150
Pole Mount




PFA151
Corner Mount








PFA120
Junction Box

Dimensions (mm)



Mounting Type

<p>Ceiling Mount PFA111 + PFB300C</p> 	<p>Junction Mount PFA111 + PFB303W + PFA120</p> 
<p>Power Box Mount PFA111 + PFB303W + PFA140</p> 	<p>Pole Mount PFA111 + PFB303W + PFA150</p> 
<p>Corner Mount PFA111 + PFB303W + PFA151</p> 	<p>Parapet Mount PFA111+ PFB303S</p> 