

DHI-LM22-F211

21.5" Full-HD LED Monitor



Features:

- Industrial level TFT LCD panel, suitable for extensive 7x24 continuous works.
- Physical resolution of 1920x1080
- High fidelity digital processing, brilliant and vivid video
- Ultra-narrow bezel design with 178°/178° wide viewing angle make your vision more open
- Built-in speakers



Technical Specification

Model

| | |
|-------|---------------|
| Model | DHI-LM22-F211 |
|-------|---------------|

System

| | |
|---------------------------------|--------------------------------|
| Diagonal | 21.5"(16:9) |
| Resolution | 1920x1080 (FHD) |
| Backlight | LED |
| Brightness/Luminance (Standard) | 250 cd/m ² |
| Contrast | 1000:1 |
| Angle of view | 178°/178°(vertical/horizontal) |
| Response Time | 14ms |
| Display Colors | 16.7M |
| VESA | 100x100 |

Signals

| | | |
|--------|-----------------------------|------|
| Input | VGA(D-Sub)x1/HDMIx1/Audiox1 | |
| Output | Speaker | 2Wx2 |

General

| | |
|------------------------|-------|
| Consumption (Standard) | 26W |
| Consumption (Standby) | ≤0.4W |

| | |
|--------------|----------------------|
| Power Supply | AC110~240V, 50/60 Hz |
|--------------|----------------------|

| | |
|------------|-------|
| Net Weight | 3.2kg |
|------------|-------|

| | |
|---------------------|--------------------|
| Dimensions(no base) | 489.8x293.7x42.7mm |
|---------------------|--------------------|

| | |
|------------------|---------------------|
| Work Environment | Temperature: 0°~40° |
| | Humidity: 10%~85% |

Accessory

| | |
|----------|----------------------------------|
| Standard | VGA cable, power cable, pedestal |
|----------|----------------------------------|

| | |
|----------|-----------------|
| Optional | Hanging bracket |
|----------|-----------------|

Dimensions(mm)

