

DHL43

43" Full-HD LCD Monitor



Features :

- Industrial level DID LCD panel, suitable for extensive 7x24 continuous works
- High fidelity digital processing, brilliant and vivid video
- Low response time, no picture ghosting
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- Infrared, RS232 double mode, supporting remote PC control
- Professional thermal design to extend equipment lifespan



Technical Specification

Model	
Model	DHL43
System	
Diagonal	43"(16:9)
Resolution	1920x1080 (FHD)
Backlight	LED
Brightness/Luminance (Standard)	450 cd/ m ²
Contrast	1100:1
Angle of view	178°/178°(vertical/horizontal)
Response time	12ms

Signals

Input	standard	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, RS232×1
	optional	Audio, RJ45, HDCVI, SDI, DP loop, USB
Output	Standard	CVBS(BNC)×2, RS232×1
	optional	Audio, DP loop

General

Consumption (Standard)	45W
Consumption (Standby)	≤1W

Power Supply	AC100~240V (+/-10%),50/60 Hz
Weight	15.5kg
Dimensions(no base)	994.5x592.7x52.9mm
Work Environment	Temperature:0 C~50 C
	Humidity:20%~90%

Accessory

Standard	VGA cable, power cable
Optional	Pedestal, hanging bracket

Dimensions(mm)

