

LM55-S401

55" UHD LED Monitor



Features :

- 4K ultra-HD resolution
- Industrial level LCD panel, suitable for 24/7 continuous works
- 4-side 5.2mm ultra-narrow bezel design
- High fidelity digital processing, brilliant and vivid video
- Built-in 3D COMB filter and 3D noise reduction
- 7ms fast response time, no image ghosting
- 16.7M color, display every details of video
- Using tamper-proof metal housing, stable and reliable
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Abundant interfaces HDMI, DVI, VGA, BNC, USB multimedia

Technical Specification

Model

Model	LM55-S401
-------	-----------

System


Diagonal	55"(16:9)
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance (Standard)	500 cd/ m ²
Contrast	4000:1
Angle of view	178°/178°(vertical/horizontal)
Response time	7ms
Display Color	8bit(16.7M)
VESA	400×400mm

Signals

Input	VGA(D-Sub)×1, CVBS(BNC)×1, DVI-D×1, HDMI×2, RS232×1, USB 2.0×1	
Output	Audio×1, RS232×1	
	Speaker	10W×2

General

Consumption (Standard)	160W
Consumption (Standby)	≤0.5W



Power Supply	AC100~240V (+/-10%), 50/60 Hz
Weight	20kg
Dimensions(no base)	1222.0×692.8×63.2mm
Work Environment	Temperature: 0℃~50℃
	Humidity: 20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Dimensions(mm)

