

DHI-NVR5208/5216/5232-4KS2

8/16/32 Channel 1U 4K&H.265 Pro Network Video Recorder



- H.265/H.264/MJPEG/MPEG4 codec decoding
- Max 320Mbps incoming bandwidth
- Up to 12Mp resolution preview&playback
- HDMI/VGA simultaneous video output
- 3D intelligent positioning with Dahua PTZ camera



System Overview

Dahua's NVR5000-4KS2 network video recorder offers an excellent performance and high recording quality for IP video surveillance applications. For applications where details are critical for identification, this professional NVR provides a powerful processor with up to 4K resolution. Additionally, the NVR features a mouse shortcut operation menu, remote management and control, centre storage, edge storage, and back up storage. Designed as a cost-effective, easy installation, this NVR is ideal for a wide range of applications such as public safety, water conservancy, transportation, city centers, education, and financial institutions. The NVR is compatible with numerous third-party devices making it the perfect solution for surveillance systems with or without a video management system (VMS). Its open architecture supports multi-user access and is compatible with ONVIF 2.4, enabling interoperability when combined with 4K cameras.

Functions

Fisheye Dewarping

The NVR features multiple fisheye dewarping modes to make viewing video easy whether its live or during playback.

4K Resolution

The NVR supports 4K ultra HD resolution (3840 x 2160) for recording, live viewing and playback.

Intelligent Video System (IVS)

Working with built-in intelligent video analytics IP cameras, the NVR has the ability to detect and analyze moving objects for improved video surveillance. The NVR provides optional standard intelligence at the edge allowing detection of multiple object behaviors such as abandoned or missing objects. IVS also supports Tripwire analytics, allowing the camera to detect when a pre-determined line has been crossed, People Counting, ideal for business intelligence, and Face Detection, for searching or identification of individuals.

Point of Sale (POS)

Ideal for grocery and retail stores, the optional POS solution allows the NVR to receive a POS transaction via corresponding video. This feature allows merchants to analyze specific transactions via the Fuzzy search Algorithm.

ANR (Automatic Network Replenishment Technology)

Video record in SD card in IP cameras when the network breaks down, and after the network recovered, the video will be transferred to NVR and then recorded in it.

Technical Specification

System

Main Processor	Quad-core embedded processor
Operating System	Embedded LINUX

Display

Interface	1 HDMI (1 HDMI up to 3840x2160), 1 VGA
Resolution	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
Multi-screen Display	8CH: 1/4/8/9 16CH: 1/4/8/9/16 32CH: 1/4/8/9/16/25/36
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

Video Detection and Alarm

Trigger Events	Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss and Tampering
Alarm input	4 Channel, Low Level Effective, Green Terminal Interface
Relay Output	2 Channel, NO/NC Programmable, Green Terminal Interface
Tracking Trigger Event	N/A

Playback and Backup

Sync Playback	8CH: 1/4/9 16/32CH: 1/4/9/16
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network

Storage

Internal HDD	2 SATA III Ports, up to 6TB capacity for each HDD
HDD Mode	Single
eSATA	N/A
SAS	N/A

Auxiliary Interface

Front Cover	N/A
USB	2 ports (1 Rear USB3.0, 1 Front USB2.0)
RS232	1 Port, for PC Communication and Keyboard
RS485	1 Port, for PTZ Control

Third-party Support

Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, and more
---------------------	--

Audio and Video

IP Camera Input	8/16/32 Channel
Two-way Talk	1 Channel Input, 1 Channel Output, RCA

Recording

Compression	H.265/H.264/MJPEG/MPEG4
Resolution	12Mp/8Mp/6Mp/5Mp/4Mp/3Mp/1080P/ 720P/D1&etc.
Record Rate	320Mbps
Bit Rate	16kbps~20Mbps for per channel
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Network

Interface	1 RJ-45 port (10/100/1000Mbps)
Ethernet Port	1 Independent 1000Mbps Ethernet Port
PoE	N/A
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.), P2P
Optical Fiber Interface	N/A
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF 2.4, CGI Conformant

Electrical

Power Supply	Single, DC12V/4A
Power Consumption	<9.5W (without HDD)

Environmental

Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH


Construction

Dimensions(W×D×H)	1U, 375mm×281.5mm×56mm (14.8" x 11.1" x 2.2")
Net Weight	1.6kg (3.5 lb) (without HDD)
Gross Weight	3.2kg(7.1 lb)(without HDD)

Certifications

CE	EN55022, EN55024, EN50130-4, EN60950-1
FCC	Part15 subpartB,ANSI C63.4-2014
UL	UL60950-1+CAN/CSA C22.2 No.60950-1

Dimensions (mm)



Ordering Information

Type	Part Number	Description
8 Channel NVR	DHI-NVR5208-4KS2	8 Channel 1U 4K&H.265 Pro Network Video Recorder
16 Channel NVR	DHI-NVR5216-4KS2	16 Channel 1U 4K&H.265 Pro Network Video Recorder
32 Channel NVR	DHI-NVR5232-4KS2	32 Channel 1U 4K&H.265 Pro Network Video Recorder
Accessories	N/A	N/A