

## VTH1510CH

## IP Indoor Monitor



Technical Specification		
Model	VTH1510CH	
System		
Main Processor	Embedded Micro Processor	
Operation System	Embedded LINUX OS	
Video		
Video Compression	H.264	
Audio		
Audio Compression	G.711	
Audio Input	All-direction Microphone	
Audio Output	Built-in Loudspeaker	
Bidirectional Talk	Support Dual-way Bidirectional talk	
Display		
LCD Screen	7" 800x480, Resisitive	
Operation Mode		
Input	Touch buttons	
Interface		
Alarm In	6	
Alarm Out	1	
RS485	1	
Network		
Ethernet	10M/100Mbps Self-adaptive	
Network Protocol	TCP/IP	
General		
Memory Slot	Micro SD, Max 32GB	

## **Features**

- 7" TFT Resistive touch screen
- · IPC surveillance
- · Alarm integration
- · Micro SD card optional, max 32GB
- · Record & Snapshot(SD card needed)





















4000	
-	
-	

Installation	Surface
Power	DC 12V/ supply directly by VTNS1060A
Power Consumption	Standby ≤1.5W, Work ≤7W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	200.5mm×136.5mm×22.0mm
Weight	0.8Kg

**Dimensions** View Area





## Application

