

VTO2000A IP Villa Outdoor Station



Technical Specification

Model	VTO2000A	
System		
Main Processor	Embedded Micro Processor	
Operation System	Embedded LINUX OS	
Video		
Video Compression	H.264	
Image Sensor	1/3" 1.3MP CMOS	
Lens	2.8mm	
Angle of View	D:120° H:90°	
Day/Night	Color Image	
Audio		
Audio Compression	G.711	
Audio Input	Omnidirectional Mic	
Audio Output	Built-in Speaker	
Bidirectional Talk	Support Dual-way Bidirectional talk	
Operation Mode		
Keypad	Single Mechanical Button	
Interface		
Door Control	2(1 relay out for main lock, 1 extended by access control module)	
Alarm In	2(1ch unlock button, 1ch feedback)	
RS485	1	
Network		
Ethernet	10M/100Mbps Self-adaptive	
Network Protocol	TCP/IP	

Features

- HD CMOS camera
- \cdot Stainless steel panel, IP54, IK07
- \cdot Night vision &Voice indication
- \cdot Video & Audio messaging
- \cdot Remote intercom with mobile APP
- · Surface mounted & Flush mounted




Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
General	
Ingress Protection	IP54, IK07
Tamper Switch	1
Installation	Surface & Flush
Material	Stainless Steel
Power	DC 12V
Power Consumption	Standby ≤1W, Work ≤10W
Working Temperature	-40°C~+60°C
Relative Humidity	10%~90%RH
Dimensions	129.9mm×32.2mm×140mm
Weight	0.8Kg


VTO2000A


Dimensions

View Area









Application

